

AXIS F1004 Sensor Unit

Super small size and price for discreet surveillance

AXIS F1004 Sensor Unit is small in size and price. It enables an affordable, highly discreet solution for the surveillance of multiple, closely situated indoor areas when used with the four-channel AXIS F44 Main Unit. AXIS F1004, which comprises a fixed lens and image sensor, provides a 102° horizontal field of view and supports HDTV 720p video when used with an AXIS F Main Unit. AXIS F1004 has a detachable 8-m (26 ft.) cable for connecting to a main unit. A flush ceiling/wall mount kit is included. Optional accessories include surface and recessed mounts.

- > **Small size and price**
- > **102° horizontal field of view**
- > **HDTV 720p**
- > **Detachable cable for easy and flexible installation**



AXIS F1004 Sensor Unit

Camera		Approvals
Image sensor	1/4" (effective) progressive scan RGB CMOS	IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 50581, IEC 60529 IP3x, EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24
Lens	Fixed iris 2.1 mm, F2.2: 102° horizontal angle of view, 56° vertical angle of view	
Minimum illumination	Color: 0.4 lux	
Shutter time	1/24500 s to 1/6 s	
Resolutions	Max: 720p	
Frame rate	25/30 fps	Dimensions
General		Weight
Casing	Zinc and plastic	Required hardware
Operating conditions	0 °C to 50 °C (32 °F to 122 °F)	Included accessories
		Optional accessories
		Warranty

More information is available at www.axis.com